



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014	~	ZQJ 11/18/2014
B	ADD P/N CODE	CJJ 11/18/2014	~	

NOTES:

- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 20mΩ Max. INITIAL.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE: 1000MΩ Min.
- ENVIRONMENT CHARACTERISTICS:
 - TEMPERATURE: -40°C~+105°C.
- PRODUCT NUMBER CODE:
LL1020-4

X	X	X	
CONTACT TYPE			
1:	TYPE 1	3:	TYPE 3
2:	TYPE 2	4:	TYPE 4
CONTACT PLATING			
F1:			Full GOLD FLASH
No. OF CONTACTS			
1*1			1*40
2*1			2*40

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE
X.	±0.60	X.	±5°	mm	DIP STRIP ADAPTER PITCH 2.54mm
.X	±0.38	.X	±3°	A4	PIN LENGTH-7.64mm/8.51mm
.XX	±0.25	.XX	±2°	SHEET SIZE	SERIES LL1020-4
DRAWING TYPE CUSTOMER				慈溪蓝翎电子有限公司 CIXI LANLING ELECTRONICS CO., LTD. Tel: 86-574-63619096 Fax: 86-574-63617070	
SCALE 1:1 SHEET 10F1					
DRAWING NO.					