





REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014	~	ZQJ 11/18/2014
B	ADD P/N CODE	CJJ 11/18/2014	~	



Technical Data
 Insulator: Black glass
 Filled polyester
 Flammability: UL 94V-0
 Sleeve: Brass CuZn36Pb3
 Current rating: 3Amps/contact max
 Contact resistance: max 10MΩ
 Dielectric strength: min 1000V/RMS
 Plating: Gold plated/Tin plated
 Operating temperature: -55°C~+105°C
 Soldering temperature: +245°C ± 5°C, 5s max

GENERAL TOLERANCE	ANGLE	TOLERANCE
X	±0.60	±5°
.X	±0.38	±3°
.XX	±0.25	±2°

DRAWING TYPE	CUSTOMER
SCALE	1:1
DRAWING NO.	10F1

PROJECTION	TITLE
UNITS	R/A&S, N, T STRIP ADAPTER
SHEET SIZE	P10C1 1.27mm
A4	LL1020-10
SERIES	

慈溪蓝翎电子有限公司
 CIXI LANLING ELECTRONICS CO., LTD.
 Tel: 86-574-65810099 Fax: 86-574-65817070