

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014		
B	ADD P/N CODE	CJJ 11/18/2014		




NOTES:

1. SPECIFICATION:
- 1.1 CONTACT RESISTANCE: 30mΩ MAX.
  - 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 250V AC(rms) FOR 1 MINUTE.
  - 1.3 INSULATION RESISTANCE: 500MΩ Min.
  - 1.4 OPERATING TEMPERATURE: -40°C~+105°C.

2. PRODUCT NUMBER CODE:

LL1044-1B-X X X X X

- PROFILE HEIGHT(DIM A):  
0:6.0mm  
1:6.47mm
- CONTACT PLATING:  
F1: FULL GOLD FLASH  
N: NICKEL
- 2: GOLD+NICKEL
- HOUSING COLOR:  
B: BLACK U:BLUE Y:YELLOW  
W: WHITE E:GREEN R:RED
- HOUSING TYPE:  
A:OPEN B:CLOSE L:Long  
2: 2pin



GENERAL TOLERANCE	ANGLE TOLERANCE	TOLERANCE
X: ±0.60	X: ±5°	±5°
.X: ±0.38	.X: ±3°	±3°
.XX: ±0.25	.XX: ±2°	±2°
DRAWING TYPE	CUSTOMER	
SCALE	1:1	SHEET 1 OF 1
DRAWING NO.	C-DS1027-XXXXX	

PROJECTION	TITLE
UNITS: mm	2.54mm MINI JUMPER CLOSE TYPE
SHEET SIZE: A4	SERIES: LL1044-1B

慈溪蓝翎电子有限公司  
 CIXI LANLING ELECTRONICS CO., LTD.  
 Tel: 86-574-88519098 Fax: 86-574-88517070