




REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014		
B	ADD P/N QDR	CJJ 11/18/2014		



Materials:
 INSULATOR: THERMOPLASTIC (UL 94V-0).
 CONTACT: COPPER ALLOY.
 CONTACT PLATED: SEE ORDERING INFORMATION.

Specifications:
 OPERATING TEMPERATURE: -40 ~ +105°C
 CONTACT RESISTANCE: 30mΩ max. (initial).
 INSULATION RESISTANCE: 500MΩ min.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 250V PER MINUTE.

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	TITLE
X, ±0.60	X, ±5°	mm	1.27mm MINI JUMPER
.X, ±0.38	.X, ±3°	A4	LL1044-4
.XX, ±0.25	.XX, ±2°		

DRAWING TYPE	CUSTOMER	SHEET	1 OF 1
SCALE	1:1		
DRAWING NO.	C-DST1027-XXXXXX		

慈溪蓝翎电子有限公司
 CIXI LANLING ELECTRONICS CO., LTD.
 Tel: 86-574-63619936 Fax: 86-574-63617070

